



## Masonry Saw ► **CHW**

Evolution of Clipper masonry saws, best known for their durability, the CHW uses an aluminium frame. This frame is very rigid and absolutely rust-proof. All the different components of the frame can be replaced. The Clipper CHW is available with two cutting length's: 500 and 600 mm.

The aluminium water tray, with an integrated slurry decanter, is removable for easy cleaning. The pivoting legs assure complete site portability. The saw is equipped with an electrical water pump. The CHW is also available with a tilting head for bevel cutting at any angle.

**Masonry Saw ▶ CHW**

**Features**

- ▶ Blade guard with removable cover provides maximum possible operator protection and permits easy access for blade changing.
- ▶ Spring-loaded, jig-welded cutting head ensures shock free cutting.
- ▶ Cutting head locking device permits easy straight through cutting.
- ▶ Improved cutting straightness due to:
  - ▶ aluminium frame
  - ▶ removable aluminium tray
  - ▶ easy to clean slurry decanter
  - ▶ jig welded conveyor cart.
- ▶ Heavy duty conveyor cart:
  - ▶ jig welded construction ensures stable and smooth operating during cutting
  - ▶ non slip top paint
  - ▶ non tipping wheels.
- ▶ Variable angle guide - cut with scale of degrees permits cutting at any angle, without additional tools.
- ▶ Electrical water pump, with switch-off for dry cutting.
- ▶ Water flow regulating valve, positioned on blade guard, reduces water consumption, and together with the water curtain, permits operator and site comfort and safety.
- ▶ Pivoting legs and transport wheels on the frame.
- ▶ Water tray and conveyor cart can be removed for easy transportation.

**Specifications**

**Model**

CHW 1.30.1	2,2 kW/3,0 HP
	115 or 230 V

Characteristics	500mm	600mm
Max. blade diam. ø	350mm	350mm
Max. depth of cut	110mm	110mm
Max. length of cut	500mm	600mm
Conveyor cart length	500mm	600mm
Conveyor cart width	500mm	500mm
Blade shaft speed	2800min <sup>-1</sup>	2800min <sup>-1</sup>
Sound pressure	73 dB(A)	73 dB(A)
Sound power	87 dB(A)	87 dB(A)

**Dimensions / Weight**

Length	1130mm	1195mm
Width	705mm	705mm
Height (total)	1350mm	1350mm
Height (folded legs)	760mm	760mm
Weight	79 kg	81 kg

**Accessory**

- ▶ Lateral extension for extra wide materials



Ergonomic working position.



Easy portability.



Conveyor cart locking and non tipping devices.



Complete and comprehensive range of diamond blades.

[www.norton-diamond.com](http://www.norton-diamond.com)

**SAINT-GOBAIN DIAMOND PRODUCTS**

Unit 2, Meridian West  
Meridian Business Park  
Leicester LE3 2WX  
England

nlesal@saint-gobain.com  
Tel.: +44 (0)116 263 23 02  
Fax: +44 (0)116 282 72 92  
Free Fax: 0800 62 23 85

Sold and supported by: